

INDUSTRIAL COMPONENT DATA

SH1603/4 065366 Y7-65366 EATON ELECTRIC Busbar support, for CI enclosure 375mm, 3x hxd 40x10mm

Brand: EATON - MOELLER | Manufacturer Part Number: SH1603/4



Manufacturer	EATON - MOELLER
MPN / Reference	SH1603/4
Catalog number	Y7-65366
Category	Busbar support
Minimum order	1 Pcs
Document ID	EO-3075CCA2F6
Generated	2026-08-04

Product Overview

Busbar support, for CI enclosure 375mm, 3x hxd=40x10mm

Bar holder, for 375mm boxes, hxd=40x10mm

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar support, for CI enclosure 375mm, 3x hxd=40x10mm

Busbar support, for use within housing side walls or within housings, component mounting possible on busbar, busbar supports clearances max. 375mm, interval between busbar centers 50mm, rated operational current $I_e=1600A$, can be used for L1, L2, L3: 3x40x10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 065366 Model Code SH1603/4 EAN 4015080653660 Product Length/Depth 15 mm Product Height 100 mm Product Width 375 mm Product Weight 0.253 kg

Compliances RoHS conform Product specifications

Special features Type Accessory for busbar enclosures

Prepared enclosures

xEnergy Safety Ci

Accessory/spare part type Busbar support Used with CI44...

L1, L2, L3: 3 x 40 x 10

CI45...

CI48...

Prepared enclosures

xEnergy Safety Ci

Accessory for busbar enclosures Current rating - max 1600 A Busbar distance 50 mm Number of poles Three-pole Distance between busbar centers 50 mm Functions Prepared enclosure

For use between two enclosures Rated operation current (Ie) 1600 A Suitable for Use between two enclosures

ETIM for 065366 Power distribution systems (EC001166)

Feature Name

Feature Value

Number of poles (EF001391)

3

Max. rated current (EF007926)

1600 A

Busbar distance (EF002638)

50 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SH1603/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.