

## INDUSTRIAL COMPONENT DATA

# +ZAV(X4)+ZVV(X4)-T0/P3 254549 Y7-254549 EATON ELECTRIC Shaft and interlock extension, L 100mm, for T0/P3. Ca..

Brand: EATON - MOELLER | Manufacturer Part Number: +ZAV(X4)+ZVV(X4)-T0/P3



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | EATON - MOELLER        |
| MPN / Reference | +ZAV(X4)+ZVV(X4)-T0/P3 |
| Catalog number  | Y7-254549              |
| Category        | Switch operating shaft |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-A0AC36D78A          |
| Generated       | 2026-08-06             |

## Product Overview

Shaft and interlock extension, L=100mm, for T0/P3. Can only be sold assembled.

+ZAV(X4)+ZVV(X4)-T0/P3

Shaft and interlock extension, L=100mm, for T0/P3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

## Additional Product Information

Shaft and interlock extension, L=100mm, for T0/P3Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, centre mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.Delivery program

Basic functionInterlock elements

shaft extensionsFunctionComplete interlock and shaft extensionsextension to 100 mm (4 x 25 mm)

When ordering with basic unitShaft length100 mmFor use withT0-.../V...

T3-.../V...

T5B-.../V...

T5-.../V...Design verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+50 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +ZAV(X4)+ZVV(X4)-T0/P3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.