

INDUSTRIAL COMPONENT DATA

+ZAV(X2)+ZVV(X2)-T0/P3 254547 Y7-254547 EATON ELECTRIC Shaft and interlock extension, L 50mm, for T0/P3. Can..

Brand: EATON - MOELLER | Manufacturer Part Number: +ZAV(X2)+ZVV(X2)-T0/P3



Manufacturer	EATON - MOELLER
MPN / Reference	+ZAV(X2)+ZVV(X2)-T0/P3
Catalog number	Y7-254547
Category	Switch operating shaft
Minimum order	1 Pcs
Document ID	EO-D878B12D08
Generated	2026-08-06

Product Overview

Shaft and interlock extension, L=50mm, for T0/P3. Can only be sold assembled.

+ZAV(X2)+ZVV(X2)-T0/P3

Shaft and interlock extension, L=50mm, for T0/P3

Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, center mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Shaft and interlock extension, L=50mm, for T0/P3Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, centre mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive

accessories complete the switch range and supplement application possibilities. Delivery program

Basic function Interlock elements

shaft extensions Function Complete interlock and shaft extension extension to 50 mm (2 x 25 mm)

When ordering with basic unit Shaft length 50 mm For use with T0-.../V...

T3-.../V...

T5B-.../V...

T5-.../V... Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +50 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +ZAV(X2)+ZVV(X2)-T0/P3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.