

INDUSTRIAL COMPONENT DATA

M22-H4 216551 Y7-216551 EATON ELECTRIC Shroud, for flush mounting plate, 4 mounting locations

Brand: EATON - MOELLER | Manufacturer Part Number: M22-H4



Manufacturer	EATON - MOELLER
MPN / Reference	M22-H4
Catalog number	Y7-216551
Category	Protective cover for command devices
Minimum order	1 Pcs
Document ID	EO-5ADAA09673
Generated	2026-08-06

Product Overview

Shroud, for flush mounting plate, 4 mounting locations

M22-H4

Eaton Moeller® series M22 Shroud, for flush mounting plate, 4 mounting locations

Shroud, insulated material, color light gray RAL 7035, for RMQ system, mounting diameter 22.3mm degree of protection IP55 in combination with flush mounting plate M22-E..., 4 knockout cable entries M20, mounting location 4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Shroud Catalog Number 216551 Model Code M22-H4 EAN

4015082165512 Product Length/Depth 110 mm Product Height 80 mm Product Width 105 mm Product Weight 0.181 kg

Compliances Bureau Veritas

CE Marked

GoST-R Certifications CSA Certified

CCC Marked

Lloyd's Register Certified

CE

CSA Class No.: 3211-03

UL 508

CSA-C22.2 No. 14-05

IEC/EN 60947-5

CSA File No.: 012528

CSA-C22.2 No. 94-91

UL

CSA

UL File No.: E29184

UL Category Control No.: NKCR Features & Functions

Color Gray Knockouts 4 x M20 (cable entry knockouts at the base) Material Insulated material light Number of locations 4

RAL-number 7035 General

Degree of protection NEMA 12

IP40 Protection Protection type only in combination with flush mounting plates M22-E... Size 22.5 mm Type Four-element

Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Veri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-H4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.