

INDUSTRIAL COMPONENT DATA

NZM4-XA110-130AC/DC 266450 Y7-266450 EATON ELECTRIC

Shunt release, 110-130VAC/DC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XA110-130AC/DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XA110-130AC/DC
Catalog number	Y7-266450
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-041CD34568
Generated	2026-08-04

Product Overview

Shunt release, 110-130VAC/DC

NZM4-XA110-130AC/DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Shunt release, 110-130VAC/DC, 4

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: switches are tripped by a voltage pulse or by the application of uninterrupted voltage. If the shunt release is energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented. undervoltage releases cannot be installed simultaneously with NZM...XHIV.. early-make auxiliary contact or NZM...XU.. shunt release. Can be used for: NZM4(-4), N(N/O)4(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 266450 Model Code NZM4-XA110-130AC/DC EAN 4015082664503 Product Length/Depth 107 mm Product Height 51 mm Product Width 64 mm Product Weight 0.256 kg

Compliances IEC

UL/CSA

RoHS conform Certifications UL (File No. E140305)

CSA (Class No. 1437-01)

CSA certified

UL489

UL listed

CSA (File No. 22086)

UL (Category Control Number DIHS)

CE marking

IEC60947

CSA-C22.2 No. 5-09 Product specifications

Type Special features Switches are tripped by a voltage pulse or by the application of uninterrupted voltage.

If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.

Shunt releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XU... undervoltage release.

Voltage rating 0.7 - 1.1 x Us 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation.

Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of the...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XA110-130AC/DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.