

INDUSTRIAL COMPONENT DATA

Z-BHASA/230 248445 Y7-248445 EATON ELECTRIC Shunt release, 110-415V, 1.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-BHASA/230



Manufacturer	EATON - MOELLER
MPN / Reference	Z-BHASA/230
Catalog number	Y7-248445
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-03501D0D3D
Generated	2026-08-05

Product Overview

Shunt release, 110-415V, 1.5HP

Z-BHASA/230

Eaton Distribution parts. Shunt release, 110-415V, 1.5HP

Shunt release, for residual current circuit-breaker unit, voltage range 110-415V AC / 110-230V DC, minimum pulse duration 10ms, standard front dimension 45 mm, mounting width 1.5 space units (27mm), top-hat rail mounting, terminal cross-section 2.5-30 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248445 Model Code Z-BHASA/230 EAN 4015082484453 Product Length/Depth 80 mm Product Height 75 mm Product Width 39.1 mm Product Weight 0.157 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Shunt release Used with Shunt releases

Accessory

Accessory for residual current circuit breaker Mounting method Can be mounted from left: Mountable residual current circuit breaker Additional equipment required Shunt release (for power circuit breaker) Ambient operating temperature - max 40 °C

Ambient operating temperature - min -5 °C Assembly width 1.5 TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC/DC Functions Shunt release (for power circuit breaker) Device fitting Miniature circuit breaker (MCB) Rated operational voltage (Ue) - max 230 V Rated switch current 1.7 A Suitable for current of main contact unit - max 3.4 A

ETIM for 248445 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Miniature circuit breaker (MCB)

Function (EF000030)

Shunt release (for power circuit breaker)

Width in number of modular spacings (EF002...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-BHASA/230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.