

INDUSTRIAL COMPONENT DATA

Z-ASA/24 248286 Y7-248286 EATON ELECTRIC Shunt release, 12-110V, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-ASA/24



Manufacturer	EATON - MOELLER
MPN / Reference	Z-ASA/24
Catalog number	Y7-248286
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-8815D1A708
Generated	2026-08-06

Product Overview

Shunt release, 12-110V, 1HP

Z-ASA/24

Shunt release, adhesive, voltage range 12-110V AC / 12-60V DC, frequency 50/60hz, standard front dimension 45 mm, mounting width 1 SU (17.5mm), DIN rail mounting, terminal cross-section 1-25 mm² can be mounted subsequently to PLS, PL6, PL7, HN, HL, PXL, PKN, P XK, PKDM, ZP-A, Z-MS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Shunt release, 12-110V, 1HPShunt release, adhesive, voltage range 12-110V AC / 12-60V DC, frequency 50/60hz, standard front dimension 45 mm, mounting width 1 SU (17.5mm), DIN rail mounting, terminal cross-section 1-25 mm² can be mounted subsequently to PLS, PL6, PL7, HN, HL, PXL, PKN, P XK, PKDM, ZP-A, Z-MS

General specificationsProduct nameEaton Distribution partsPart no.Z-ASA/24EAN4015082482862Product Length/Depth80 millimetreProduct height75 millimetreProduct width26.2 millimetreProduct weight0.092 kilogramCompliancesRoHS conformCertificationsNOM-NYCE

EN45545-2

IEC 61373Product TradenameNoneProduct TypeDistribution partsProduct Sub TypeNonePublic ConsumptionYesProduct Family DescriptionES-PMCC-PDC-Eaton Distribution partsGlobally MarketableYesProduct Specification DetailsAccessory/spare part typeShunt releaseAdditional equipment requiredShunt release (for power circuit breaker)Ambient operating temperature - max40 °CAmbient operating temperature - min-5 °CAppliationSwitchgear for

industrial and advanced commercial applicationsAssembly width1Device fittingOtherFunctionsShunt release (for power circuit breaker)Number of contacts (change-over contacts)0Number of contacts (normally closed contacts)1Number of contacts (normally open contacts)1Number of poles at main contact unit - max1Number of switches (fault signal)0Rated operational voltage (Ue) - max24 VRated switch current0 ASuitable for current of main contact unit - max15
ATypeAccessory
Accessory for combined residual c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-ASA/24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.