

INDUSTRIAL COMPONENT DATA

ZP-ASA/24 248438 Y7-248438 EATON ELECTRIC Shunt release, 12-110V, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: ZP-ASA/24



Manufacturer	EATON - MOELLER
MPN / Reference	ZP-ASA/24
Catalog number	Y7-248438
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-B78AB5176E
Generated	2026-08-05

Product Overview

Shunt release, 12-110V, 1HP

ZP-ASA/24

Eaton Distribution parts. Shunt release, snap-fit, 12-110V AC / 12-60V DC, 50/60hz, front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-25 mm²

Shunt release, snap-fit, voltage range 12-110V AC / 12-60V DC, frequency 50/60hz, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-25 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248438 Model Code ZP-ASA/24 EAN 4015082484385 Product Length/Depth 80 mm Product Height 75 mm Product Width 26.2 mm Product Weight 0.087 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Shunt release Used with Shunt releases

Accessory

Accessory for combined residual current/power circuit breaker

Accessory for miniature circuit breaker Mounting method For fitting on left to: FAZ, FRBmM-1N, Z-MS Additional equipment

required Shunt release (for power circuit breaker) Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 1 TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC Functions Shunt release (for power circuit breaker) Device fitting Other Rated operational voltage (Ue) - max 24 V Rated switch current 0 A Suitable for current of main contact unit - max 15 A ETIM for 248438 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Other

Function (EF000030)

Shunt release (for power circuit breaker)

Width in number of modular spacings (EF002950)

1

Number of contacts as norm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZP-ASA/24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.