

INDUSTRIAL COMPONENT DATA

+IZMX-STS24DC 123731 EATON ELECTRIC Shunt release (for power circuit breaker) (2) 24VDC

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-STS24DC



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-STS24DC
Catalog number	123731
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-F3BBDB7BDF
Generated	2026-08-03

Product Overview

Shunt release (for power circuit breaker);(2) 24VDC

Suitable for remote switching off, cannot be combined with an undervoltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX shunt release Catalog Number 123731 Model Code +IZMX-STS24DC EAN 4015081213368 Product Length/Depth 150 mm Product Height 100 mm Product Width 100 mm Product Weight 0.113 kg

Compliances RoHS conform Delivery program

Type Accessory Accessory/spare part type Remote switching Technical data - electrical

Voltage type DC Control voltage operating range 0.7 - 1.1 x Us

24 V DC Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V

Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated

control supply voltage (Us) at DC - min 24 V Rated control supply voltage (Us) at DC - max 24 V Current rating - max 0.18

A (maximum holding current) Rated operational current 0.18 A (maximum holding current) Adjustment range undelayed

short-circuit release (end value) - max 0 A Power consumption 5 VA/W AC/DC Pick-up power consumption at 35 ms - max

500 VA/W Circuit breaker total switching time 22 ms (Us = 100%) Initial value of the undelayed short-circuit release - min 0

A Technical data - mechanical

Number of actuation per minute - max 3 Number of contacts (change-over contacts) 0 Number of contacts (normally closed)

contacts) 0 Number of contacts (normally open contacts) 0 Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-STS24DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.