

INDUSTRIAL COMPONENT DATA

+IZMX-STS60DC 124059 EATON ELECTRIC Shunt release (for power circuit breaker) (2) 60VDC

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-STS60DC



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-STS60DC
Catalog number	124059
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-CF52F5F095
Generated	2026-08-02

Product Overview

Shunt release (for power circuit breaker);(2) 60VDC

Suitable for remote switching off, cannot be combined with an undervoltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX shunt release Catalog Number 124059 Model Code +IZMX-STS60DC EAN 4015081216642 Product Length/Depth 150 mm Product Height 100 mm Product Width 100 mm Product Weight 0.113 kg

Compliances CE Marked

RoHS conform Delivery program

Type Accessory Accessory/spare part type Remote switching Technical data - electrical

Voltage type DC Control voltage operating range 60 V DC

0.7 - 1.1 x Us Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 60 V Rated control supply voltage (Us) at DC - max 60 V Current rating - max 0.07 A (maximum holding current) Rated operational current 0.07 A (maximum holding current) Adjustment range undelayed short-circuit release (end value) - max 0 A Power consumption 5 VA/W AC/DC Pick-up power consumption at 35 ms - max 540 VA/W Circuit breaker total switching time 22 ms (Us = 100%) Initial value of the undelayed short-circuit release - min 0 A Technical data - mechanical

Number of actuation per minute - max 3 Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature - min -25 °C Ambient operating temperature -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-STS60DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.