

INDUSTRIAL COMPONENT DATA

NZM1-XAHIV208-250AC/DC 259782 Y7-259782 EATON ELECTRIC Shunt release, 208-240VAC/DC, +1early N/O

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XAHIV208-250AC/DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XAHIV208-250AC/DC
Catalog number	Y7-259782
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-F0A4A1846A
Generated	2026-08-06

Product Overview

Shunt release, 208-240VAC/DC, +1early N/O

NZM1-XAHIV208-250AC/DC

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: cannot be used in conjunction with NZM...-XR... remote operator. If the shunt release is energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented. early make of auxiliary contact on switching on and off (manual operation): approx. 20ms . Undervoltage releases cannot be installed simultaneously with NZM...-XHIV.. early-make auxiliary contact or NZM...-XU.. shunt release. Can be used for: NZM1(-4), N(N/O)1(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Shunt release, 208-240VAC/DC, +1early N/OOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: cannot be used in conjunction with NZM...-XR... remote operator. If the shunt release is energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented. early make of auxiliary contact on switching on and off (manual operation): approx. 20ms. Undervoltage releases cannot be installed simultaneously with NZM...-XHIV.. early-make auxiliary contact or NZM...-XU.. shunt release. Can be used for: NZM1(-4), N(N/O)1(-4)Delivery program
Product rangeAccessoriesAccessoriesShunt releaseAccessoriesShunt releasesStandard/ApprovalUL/CSA,

IEC Construction size NZM1 Description Cannot be used in conjunction with NZM...-XR... remote operator.
If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.
Early make of auxiliary contact on switching on and off (manual operation): approx. 20 ms.
Shunt releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XU...
undervoltage release. Connection type with terminal block on the left-hand switch side Auxiliary contacts with early-make
auxiliary contact Rated control voltage [Us] 208 - 250 V AC/DC V For use with NZM1(-4), N(S)1(-4) Technical data
Shunt release Ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XAHIV208-250AC/DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.