

INDUSTRIAL COMPONENT DATA

A-PKZ0(240V60HZ) 073198 Y7-73198 EATON ELECTRIC 073198 A-PKZ0(240V60HZ)

Brand: EATON - MOELLER | Manufacturer Part Number: A-PKZ0(240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	A-PKZ0(240V60HZ)
Catalog number	Y7-73198
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-6B90E992CD
Generated	2026-08-05

Product Overview

073198 A-PKZ0(240V60HZ)

Trigger coil; Shunt; 240 V 60 Hz

Eaton Moeller® series A-PKZ0 Shunt release (for power circuit breaker), 240 V 60 Hz, Standard voltage, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE

Shunt release with screw terminals, for circuit-breaker PKZ(M)0 size

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ Shunt release Catalog Number 073198 Model Code A-PKZ0(240V60HZ) EAN 4015080731986 Product Length/Depth 68 mm Product Height 90 mm Product Width 24 mm Product Weight 0.13 kg

Certifications CE

CSA

UL

CSA File No.: 165628

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA-C22.2 No. 14

IEC/EN 60947-4-1

UL 508

UL File No.: E36332 Features & Functions

Electric connection type Screw connection General

Product category Accessories Suitable for Motor safety switch Used with Motor protective circuit-breaker Voltage type AC
Ambient conditions, mechanical

Mounting position Can be fitted to left side of the motor protection switch Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 1 x (0.75 - 2.5) mm²

2 x (0.75 - 2.5) mm² Terminal capacity (solid/stranded AWG) 1 x (18 - 14)

2 x (18 - 14) Electrical rating

Operational voltage 0.7- 1.1 x Us (DC)

0.7- 1.1 x Us (alternating voltage)

0.7 - 1.1 x Us (AC) Rated operational voltage (Ue) at AC - min 42 V Rated operational voltage (Ue) at AC - max 480 V

Rated operational voltage (Ue) at DC - min 24 V Rated operational voltage (Ue) at DC - max 250 V Magnet system

Operational voltage 0.7- 1.1 x Us (DC)

0.7- 1.1 x Us (alternating voltage)

0.7 - 1.1 x Us (AC) Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / A-PKZ0(240V60HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.