

INDUSTRIAL COMPONENT DATA

NZM1-XA380-440AC/DC 259728 Y7-259728 EATON ELECTRIC

Shunt release, 380-440VAC/DC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XA380-440AC/DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XA380-440AC/DC
Catalog number	Y7-259728
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-4387ED6C25
Generated	2026-08-04

Product Overview

Shunt release, 380-440VAC/DC

NZM1-XA380-440AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Shunt release, 380-440VAC/DCOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups.

Notes: switches are tripped by a voltage pulse or by the application of uninterrupted voltage. If the shunt release is energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented.undervoltage releases cannot be installed simultaneously with NZM...XHIV.. early-make auxiliary contact or NZM...XU.. shunt release. Can be used for: NZM1(-4), N(N/O)1(-4)Delivery program

Product rangeAccessoriesAccessoriesShunt releaseAccessoriesShunt releasesStandard/ApprovalUL/CSA, IECConstruction sizeNZM1DescriptionSwitches are tripped by a voltage pulse or by the application of uninterrupted voltage. If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.

Shunt releases cannot be installed simultaneously with NZM...XHIV... early-make auxiliary contact or NZM...XU... undervoltage release.Connection typewith terminal block on the left-hand switch sideAuxiliary contactswithout auxiliary

contactRated control voltage [Us]380 - 440 V AC/DC VFor use withNZM1(-4), N(S)1(-4)Technical data

Shunt releaseRated control voltage [Us]AC [Us]380-440 V ACRated control voltage [Us]DC [Us]380-440 V

DCFrequency50/60/200/400, DC HzOperating rangeAC [x Us]0.7 - 1.1Operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XA380-440AC/DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.