

INDUSTRIAL COMPONENT DATA

**A-PKZ0(380V50HZ) 073189 Y7-73189 EATON ELECTRIC
073137 U-PKZ0(380V50HZ)**

Brand: EATON - MOELLER | Manufacturer Part Number: A-PKZ0(380V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	A-PKZ0(380V50HZ)
Catalog number	Y7-73189
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-364AD868DE
Generated	2026-08-04

Product Overview

073137 U-PKZ0(380V50HZ)

Trigger coil; Shunt; 380 V 50 Hz

Shunt release (for power circuit breaker), 380 V 50 Hz, Standard voltage, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE

Shunt release with screw terminals, for circuit-breaker PKZ(M)0 size

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product InformationShunt release (for power circuit breaker), 380 V 50 Hz, Standard voltage, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE
Shunt release with screw terminals, for circuit-breaker PKZ(M)0 size

General specificationsProduct nameEaton Moeller® series PKZ Shunt releasePart

no.A-PKZ0(380V50HZ)EAN4015080731894Product Length/Depth68 millimetreProduct height90 millimetreProduct width24 millimetreProduct weight0.129 kilogramCertificationsUL 508

CSA Class No.: 3211-05

CSA File No.: 165628

CSA-C22.2 No. 14

CE

UL

UL Category Control No.: NLRV

UL File No.: E36332

CSA

IEC/EN 60947-4-1Product TradenameA-PKZ0Product TypeAccessoryProduct Sub TypeShunt releaseCatalog NotesCannot be combined with U-PKZ0 undervoltage release

Cannot be combined with undervoltage release U-PKZ0Features & FunctionsElectric connection typeScrew connectionGeneral informationProduct categoryAccessoriesSuitable forMotor safety switchUsed withMotor protective circuit-breakerVoltage typeACAmbient conditions, mechanicalMounting positionCan be fitted to left side of the motor protection switchClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max55 °CTerminal capacitiesTerminal capacity (solid/flexible with ferrule)2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²Terminal capacity (solid/stranded AWG)1 x (18 - 14)

2 x (18 - 14)Electrical ratingOperational voltage0.7- 1.1 x Us (DC)

0.7 - 1.1 x Us (AC)

0.7- 1.1 x Us (alternating voltage)Rated operational voltage (Ue...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / A-PKZ0(380V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.