

INDUSTRIAL COMPONENT DATA

NZM-XCM 229413 Y7-229413 EATON ELECTRIC Shunt release, for capacitor unit

Brand: EATON - MOELLER | Manufacturer Part Number: NZM-XCM



Manufacturer	EATON - MOELLER
MPN / Reference	NZM-XCM
Catalog number	Y7-229413
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-C7F993F3A6
Generated	2026-08-04

Product Overview

Shunt release, for capacitor unit

NZM-XCM

Eaton Moeller series NZM - Molded Case Circuit Breaker. Shunt release, for capacitor unit

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: capacitor unit 230 V 50/60 Hz in conjunction with NZM...-XA208-250 AC/DC shunt release. Enclosure: degree of protection IP20. Not UL/CSA approved. enables the safe use of circuit-breakers as mesh network circuit-breakers in the range from 0-110 % Un with constant switch-off time of 40ms. If the mains voltage is absent, the installed capacitor supplies power for actuating the shunt release for at least 12 hours . The configuration of the capacitor unit is undertaken independently of the circuit-breaker. Connect capacitor unit to the supply side. engineering Guidelines: Con

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 229413 Model Code NZM-XCM EAN 4015082294137

Product Length/Depth 100 mm Product Height 114 mm Product Width 74 mm Product Weight 0.48 kg Compliances IEC RoHS conform Product specifications

Used with NZM2(-4), N(S)2(-4)

NZM3(-4), N(S)3(-4)

NZM1(-4), N(S)1(-4)

NZM4(-4), N(S)4(-4) Type Special features Capacitor unit 230 V 50/60 Hz in conjunction with NZM...-XA208-250 AC/DC shunt release

Enclosure: degree of protection IP20

not UL/CSA approved

Enables the safe use of circuit-breakers as mesh network circuit-breakers in the range from 0 - 110 % Un with constant switch-off time of 40 ms.

If the mains voltage is absent, the installed capacitor supplies power for actuating the shunt release for at least 12 hours.

The configuration of the capacitor unit is undertaken independently of the circuit-breaker.

Connect capacitor unit to the supply side!

Engineering Guidelines: Connect a standard auxiliary contact as N/O in series with the shunt release!

Standard auxiliary contact not included as standard.

10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat

dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the

switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM-XCM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.