

INDUSTRIAL COMPONENT DATA

Z-ASA/230 248287 Y7-248287 EATON ELECTRIC Shunt release (for power circuit breaker), 110-415V AC

Brand: EATON - MOELLER | Manufacturer Part Number: Z-ASA/230



Manufacturer	EATON - MOELLER
MPN / Reference	Z-ASA/230
Catalog number	Y7-248287
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-7AB1E63B38
Generated	2026-08-06

Product Overview

Shunt release (for power circuit breaker), 110-415V AC

Z-ASA/230

Eaton Distribution parts. Shunt release (for power circuit breaker), 110-415V AC

Remote tripping unit for retrofitting on PLS, CLS6, PKN, PKDM, Z-A40, Z-MS, module width 1TE, standard auxiliary contacts can also be mounted in addition, status indication red/green, type ZP-ASA snap-fit, type Z-ASA adhesive

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248287 Model Code Z-ASA/230 EAN 4015082482879 Product Length/Depth 80 mm Product Height 75 mm Product Width 18 mm Product Weight 0.106 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Shunt release Used with Shunt releases

Accessory for combined residual current/power circuit breaker

Accessory

Accessory for miniature circuit breaker Mounting method For fitting on left to: FAZ, FRBmM-1N, Z-MS Additional equipment required Shunt release (for power circuit breaker) Ambient operating temperature - max 75 °C Ambient operating

temperature - min -35 °C Assembly width 1 TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC Functions Shunt release (for power circuit breaker) Device fitting Other Rated operational voltage (Ue) - max 415 V Rated switch current 0 A Suitable for current of main contact unit - max 15 A ETIM for 248287 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Other

Function (EF000030)

Shunt release (for power circuit breaker)

Width in number of modular spacings (EF002950)

1

Number of contacts as norm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-ASA/230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.