

INDUSTRIAL COMPONENT DATA

A-PKZ0(*V60HZ) 982166 EATON ELECTRIC Star-delta contactor combination, 132kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: A-PKZ0(*V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	A-PKZ0(*V60HZ)
Catalog number	-
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-141B605F49
Generated	2026-08-06

Product Overview

Star-delta contactor combination, 132kW/400V/AC3

Trigger coil; Shunt; *V 60 Hz

Shunt release (for power circuit breaker), ...V 60 Hz (24 - 600 V), Non-standard voltages outside standard voltages, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE

Shunt release with screw terminals, for circuit-breaker PKZ(M)0 size, non-standard voltage

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Motor-protective circuit-breakers PKZ (Accessories)

Additional Product Information

Shunt release (for power circuit breaker), ...V 60 Hz (24 - 600 V), Non-standard voltages outside standard voltages, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE
Shunt release with screw terminals, for circuit-breaker PKZ(M)0 size, non-standard voltage
Delivery program

Product rangeAccessoriesAccessoriesShunt releaseActuating voltage...V 60 Hz (24 - 600 V)Voltage typeNon-standard voltages outside standard voltagesCurrent actuationACContact sequenceConnection techniqueScrew terminalsFor use withShunt release PKZ0(4), PKEFor use withPKZM0

PKZM4

PKZM0-T

PKM0

PKZM01

PKEFor non-standard voltages, the required actuation voltage from the specified range (...-...V) must be indicated in the *

for the part no. Notes Can be fitted to the left of:

Motor protective circuit-breaker

Cannot be combined with:

U-PKZ0 undervoltage release Technical data

General Terminal capacities Solid or flexible conductor, with ferrule 1 x (0,75 - 2,5)

2 x (0,75 - 2,5) mm² Terminal capacities Solid or stranded 1 x (18 - 14)

2 x (18 - 14) AWG Actuating voltage... V 60 Hz (24 - 600 V) Operating range Alternating voltage 0.7- 1.1 x U_S Power

consumption AC Pull-in power [Pick-up] 5 VA AC Sealing power [Sealing] 3 VA Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [I_n] 0 A Heat dissipation per

pole, current-dependent [P_{vid}] 0 W Equipment heat dissipation, current-dependent [P_{vid}] 0 W Static heat dissipation,

non-current-dependent [P_{vs}] 0.5 W Heat....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / A-PKZ0(*V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.