

INDUSTRIAL COMPONENT DATA

Z-LHASA/230 248442 Y7-248442 EATON ELECTRIC Shunt release, up to 125 A, 110-415V, 1.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-LHASA/230



Manufacturer	EATON - MOELLER
MPN / Reference	Z-LHASA/230
Catalog number	Y7-248442
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-CA90E89FA6
Generated	2026-08-06

Product Overview

Shunt release, up to 125 A, 110-415V, 1.5HP

Z-LHASA/230

Eaton Distribution parts. Shunt release, up to 125A, 110-415V, 1.5HP

Shunt release, for MCB up to 125A, voltage range 110-415V AC, max. current consumption at switch-on time $I_{on} 2 A$, frequency 50/60hz, can be retrofitted, standard front dimension 45 mm, mounting width 1.5 space units (27mm), top-hat rail mounting, terminal cross-section 1-25 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts

Catalog Number 248442

Model Code Z-LHASA/230

EAN 4015082484422

Product Length/Depth 80 mm

Product Height 75 mm

Product Width 39.1 mm

Product Weight 0.158 kg

Compliances RoHS conform

Certifications EN45545-2

IEC 61373

Product specifications

Used with Shunt releases

Accessory/spare part type Shunt release

Mounting method For fitting on left to: AZ

Additional equipment required Shunt release (for power circuit breaker)

Ambient operating temperature - max 40 °C

Ambient operating temperature - min -5 °C

Assembly width 1.5 TE

Number of contacts (change-over contacts) 0

Number of contacts (normally closed contacts) 1

Number of contacts (normally open contacts) 1

Number of poles at main contact unit - max 1

Number of switches (fault signal) 0

Voltage type AC

Functions Shunt release (for power circuit breaker)

Device fitting Miniature circuit breaker (MCB)

Type Accessory

Accessory for miniature circuit breaker

Application Switchgear for industrial and advanced commercial applications

Rated operational voltage (Ue) - max 230 V

Rated switch current 2 A

Suitable for current of main contact unit - max 2 A

ETIM for 248442 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Miniature circuit breaker (MCB)

Function (EF000030)

Shunt release (for power circuit breaker)

Width in number of modular spacings (EF002950)

1.5

Number of contacts as normally open contact (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-LHASA/230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.