


INDUSTRIAL COMPONENT DATA

AZ-XAA(110-415VAC) 212059 Y7-212059 EATON ELECTRIC Shunt release, up to 125 A, 110-415V, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: AZ-XAA(110-415VAC)



Manufacturer	EATON - MOELLER
MPN / Reference	AZ-XAA(110-415VAC)
Catalog number	Y7-212059
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-D47BFD6CBF
Generated	2026-08-06

Product Overview

Shunt release, up to 125 A, 110-415V, 1HP

AZ-XAA(110-415VAC)

Eaton Distribution parts. Shunt release, up to 125A, 110-415V, 1HP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 212059 Model Code AZ-XAA(110-415VAC) EAN 4015082120597
Product Length/Depth 80 mm Product Height 75 mm Product Width 39.1 mm Product Weight 0.158 kg Compliances RoHS conform Product specifications

Type Special features IP20 (switch) Accessory/spare part type Shunt release Degree of protection IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Accessory for miniature circuit breaker

Accessory Admissible back-up fuse Inherently short-circuit-proof Mounting method Top-hat rail IEC/EN 60715 Additional equipment required Shunt release (for power circuit breaker) Terminal protection Protection against electric shock to IEC 536 Terminal type Twin-purpose terminals Voltage range 110 V AC - 415 V AC Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 1 TE Enclosure width 90 mm Inrush current at AC 38 A Inrush current at DC 34 A Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Pick-up time AC 2.1 ms Rated insulation voltage (Ui) 440 VAC Voltage type AC/DC Functions Shunt release (for power

circuit breaker) Duty factor 2 ms Device fitting Miniature circuit breaker (MCB) Mounting width 17.5 mm (1 space unit)
Lifespan, mechanical 4000 operations Rated operational volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AZ-XAA(110-415VAC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.