

INDUSTRIAL COMPONENT DATA

FAZ-XAA-C-110-415VAC 278519 Y7-278519 EATON ELECTRIC

Shunt release, up to 63 A, 110-415V, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-XAA-C-110-415VAC



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-XAA-C-110-415VAC
Catalog number	Y7-278519
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-716A1BEFE2
Generated	2026-08-06

Product Overview

Shunt release, up to 63 A, 110-415V, 1HP

FAZ-XAA-C-110-415VAC

Eaton Distribution parts. Shunt release, up to 63A, 110-415V, 1HP

Shunt release, for MCB up to 63A, voltage range 110-415V AC, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-2.5 mm² solid and flexible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 278519 Model Code FAZ-XAA-C-110-415VAC EAN

4015082785192 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 17.7 mm Product Weight 0.087 kg

Compliances RoHS conform Certifications EN45545-2

IEC 61373 Catalog Notes 0-415VAC) Product specifications

Type Accessory/spare part type Shunt release Degree of protection IP40 Frame Standard front dimension: 45 mm

Frequency rating 50 Hz / 60 Hz Used with Accessory for miniature circuit breaker

Accessory Mounting method Top-hat rail IEC/EN 60715 Additional equipment required Shunt release (for power circuit breaker) Terminal protection Protection against electric shock to IEC 536 Terminal type Twin-purpose terminals Voltage

range 110 V AC - 415 V AC Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C

Assembly width 1 TE Enclosure width 80 mm Number of contacts (change-over contacts) 0 Number of contacts (normally

closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC Functions Shunt release (for power circuit breaker) Device fitting Miniature circuit breaker (MCB) Mounting width 17.5 mm (1 space unit) Rated operational voltage (Ue) - max 110 V Rated switch current 0 A Suitable for current of main contact unit - max 0 A Terminal capacity (cable) 1 mm² - 2.5 mm² Terminal capacity (solid wire) 1 mm² - 2.5 mm²
ETIM f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-XAA-C-110-415VAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.