

INDUSTRIAL COMPONENT DATA

NZM2/3-XA480-525AC/DC 259768 Y7-259768 EATON ELECTRIC Shunt release (for power circuit breaker), 480-525VAC/..

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XA480-525AC/DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XA480-525AC/DC
Catalog number	Y7-259768
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-5700D90BE6
Generated	2026-08-05

Product Overview

Shunt release (for power circuit breaker), 480-525VAC/DC

NZM2/3-XA480-525AC/DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Shunt release (for power circuit breaker), 480-525VAC/DC

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: switches are tripped by a voltage pulse or by the application of uninterrupted voltage. If the shunt release is energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented. undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XU.. shunt release. Can be used for: NZM2(-4), N(N/O)2(-4), NZM3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 259768 Model Code NZM2/3-XA480-525AC/DC EAN 4015082597689 Product Length/Depth 42 mm Product Height 90 mm Product Width 30 mm Product Weight 0.064 kg

Compliances IEC

UL/CSA

RoHS conform Product specifications

Type Special features Switches are tripped by a voltage pulse or by the application of uninterrupted voltage.

If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.

Shunt releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XU... undervoltage release.

10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XA480-525AC/DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.