

INDUSTRIAL COMPONENT DATA

**SL20,MNM,IP42,200lm,3H SL2MNM42F3C3A EATON
ELECTRIC SI20 foundation,MNM,IP42,200lm,3H**

Brand: EATON - MOELLER | Manufacturer Part Number: SL20,MNM,IP42,200lm,3H



Manufacturer	EATON - MOELLER
MPN / Reference	SL20,MNM,IP42,200lm,3H
Catalog number	SL2MNM42F3C3A
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-36BCA0D91F
Generated	2026-08-06

Product Overview

SI20 foundation,MNM,IP42,200lm,3H

SL20,MNM,IP42,200lm,3H

Eaton SafeLite, Safety lighting/ exit sign, 20m viewing distance, Escape route and open area, Stand alone, LED, Maintained / Non-Maintained operation, 60lm in mains, IP42, 200lm, 3 hour duration, 3 ISO pictograms (D,L,R)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Self Contained -Safe Lite

Additional Product Information

ETIM for SL2MNM42F3C3A Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounting/recessed mounting

Suitable for labelling type (EF001277)

Sticker

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

None

With remote switch connection (EF007947)

No

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

NiCd

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Suitable for number of light sources (EF006436)

1

Lamp holder (EF000048)

None

Number of lighting heads (EF004258)

8

Housing material (EF001596)

Plastic

Housing colour (EF000136)

White

Material cover (EF004284)

Plastic transparent

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

Electronic transformer

Light distributor (EF012170)

Reflector

Degree of protection (IP) (EF005474)

IP42

Impact strength (EF004293)

IK04

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

5 °C

Max. system power (EF009347)

3.2 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

200 lm

Luminous flux in standby mode (EF011954)

60 lm

Colour temperature (EF009346)

6500 K

Power factor (EF025740)

0.84

Recognition distance (EF008732)

20 m

Nominal operation time (EF012518)

3 h

Width (EF000008)

119 mm

Height/depth (EF001456)

49 mm

Length (EF001438)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL20,MNM,IP42,200Im,3H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.