

INDUSTRIAL COMPONENT DATA

**SL20,MNM,IP65,200lm,3H SL2MNM65F3C3A EATON
ELECTRIC SI20 foundation,MNM,IP65,200lm,3H**

Brand: EATON - MOELLER | Manufacturer Part Number: SL20,MNM,IP65,200lm,3H



Manufacturer	EATON - MOELLER
MPN / Reference	SL20,MNM,IP65,200lm,3H
Catalog number	SL2MNM65F3C3A
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-E20116CA0C
Generated	2026-08-05

Product Overview

SI20 foundation,MNM,IP65,200lm,3H

SL20,MNM,IP65,200lm,3H

Eaton SafeLite, Safety lighting/ exit sign, 20m viewing distance, Escape route and open area, Stand alone, LED, Maintained / Non-Maintained operation, 60lm in mains, IP65, 200lm, 3 hour duration, 3 ISO pictograms (D,L,R)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Self Contained -Safe Lite

Additional Product Information

General specifications

Product Name Eaton SafeLite SC Emergency Luminaire Catalog Number SL2MNM65F3C3A Ean 3660191604530 Product Length/Depth 270 mm Product Height 49 mm Product Width 119 mm Product Weight 0.675 kg Certifications Ec Product Specifications

Battery voltage 3.6 V Battery quality NiCd Glow wire test 850 °C Permissible ambient temperature - min 5 °C Permissible ambient temperature - max 40 °C Protection class II Degree of impact resistance (IK) IK 07 Outdoor use compliance False Explosion protected False Diameter 9999 in Degree of protection IP65 Mode Maintained / Non-Maintained (M/NM) Lamp type LED not exchangeable With light source True Lamp holder None, 19 Lamp power 4.2 W Type of indicator Only single-sided Monitoring equipment None, 19 Power supply system Peripheral (individual battery) Circuit Other Voltage type Ac Nominal current - max 3 mA Nominal current - min 3 mA Power factor .84 Wiring system Continuous circuit/emergency circuit With remote switch connection False Connection type Plug-in connection Max. system power 3.2 W Rated life time L70/B10 at 25 °C 60000 hour Type of control gear Electronic transformer Nominal voltage AC - max 240 V Nominal voltage

AC - min 220 V Rated ambient temp acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max 40 °C
Nominal operation time - min 3 hour Nominal operation time - max 3 hour Autonomy 3 hours Mounting Method Surface
mounting/recessed mounting Material housing Plastic Color housing White Mater...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL20,MNM,IP65,200Im,3H with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.