

INDUSTRIAL COMPONENT DATA

SL20,MNM,IP65,300lm,1H SL2MNM65H1C EATON ELECTRIC SAFELITE,20M,IP65,300LM,1H

Brand: EATON - MOELLER | Manufacturer Part Number: SL20,MNM,IP65,300lm,1H



Manufacturer	EATON - MOELLER
MPN / Reference	SL20,MNM,IP65,300lm,1H
Catalog number	SL2MNM65H1C
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-C06752C54E
Generated	2026-08-02

Product Overview

SAFELITE,20M,IP65,300LM,1H

SL20,MNM,IP65,300lm,1H

Eaton SafeLite, Safety lighting/ exit sign, 20m viewing distance, Escape route and open area, Stand alone, LED, Maintained / Non-Maintained operation, 60lm in mains, IP65, 300lm, 1 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self Contained -Safe Lite
--------------	---

Additional Product Information

General specifications

Product Name Eaton SafeLite SC Emergency Luminaire Catalog Number SL2MNM65H1C Ean 3660191609597 Product Length/Depth 270 mm Product Height 49 mm Product Width 119 mm Product Weight 0.499 kg Certifications Ec Product Specifications

Battery voltage 3.6 V Battery quality NiCd Protection class II Degree of protection IP65 Lamp type LED not exchangeable With light source True Lamp holder None, 19 Type of indicator Only single-sided Monitoring equipment None, 19 Power supply system Peripheral (individual battery) Voltage type Ac Power factor .74 Wiring system Continuous circuit/emergency circuit With remote switch connection False Connection type Plug-in connection Max. system power 3.2 W Rated life time L70/B10 at 25 °C 60000 hour Type of control gear Electronic transformer Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Rated ambient temp acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max 40 °C Nominal operation time - min 1 hour Nominal operation time - max 1 hour Mounting Method Surface mounting/recessed mounting Material housing Plastic Color housing White Material cover Plastic, transparent Labelling type Insert sheet/plate

Pictogram included False Built-in Length 270 mm Built-in Width 119 mm Built-in height/depth 49 mm Number Of Poles (numeric) 2 Impact strength IK07 Rated Luminous Flux Acc. IEC 62722-2-1 300 lm Color temperature - max 6500 K Color temperature - min 6500 K Light distributor Reflector Energy efficienc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL20,MNM,IP65,300lm,1H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.