

INDUSTRIAL COMPONENT DATA

SL30,MNM,IP42,200lm,1H SL3MNM42F1C3A EATON ELECTRIC SL30,MNM,IP42,200lm,1H

Brand: EATON - MOELLER | Manufacturer Part Number: SL30,MNM,IP42,200lm,1H



Manufacturer	EATON - MOELLER
MPN / Reference	SL30,MNM,IP42,200lm,1H
Catalog number	SL3MNM42F1C3A
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-DB2E1EF6F1
Generated	2026-08-05

Product Overview

SL30,MNM,IP42,200lm,1H

Eaton SafeLite, Safety lighting/ exit sign, 30m viewing distance, Escape route and open area, Stand alone, LED, Maintained / Non-Maintained operation, 60lm in mains, IP42, 200lm, 1 hour duration, 3 ISO pictograms (D,L,R)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Self Contained -Safe Lite**

Additional Product Information

ETIM for SL3MNM42F1C3A Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounting/recessed mounting

Suitable for labelling type (EF001277)

Sticker

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

None

With remote switch connection (EF007947)

No

Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
12
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
Electronic transformer
Light distributor (EF012170)
Reflector
Degree of protection (IP) (EF005474)
IP42
Impact strength (EF004293)
IK04
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
2.7 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
200 lm
Luminous flux in standby mode (EF011954)
60 lm
Colour temperature (EF009346)
6500 K
Power factor (EF025740)

0.96

Recognition distance (EF008732)

30 m

Nominal operation time (EF012518)

1 h

Width (EF000008)

170 mm

Height/depth (EF001456)

62 mm

Length (EF001438)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL30,MNM,IP42,200Im,1H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.