

INDUSTRIAL COMPONENT DATA

SL4-PIB-800 177313 Y7-177313 EATON ELECTRIC Signal column D 40 mm Base Module 800 mm Tube and foot

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-PIB-800



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-PIB-800
Catalog number	Y7-177313
Category	Connection module for signal tower
Minimum order	1 Pcs
Document ID	EO-B8C35F8754
Generated	2026-08-06

Product Overview

Signal column; D=40 mm; Base Module; 800 mm; Tube and foot

SL4-PIB-800

Base module; 800-mm aluminum tube and foot

Base module, Color black, Aluminum color tube, Product range: SL signal towers, Connection technique: Push in terminals, Mounting type: for horizontal mounting, Fitted with: Base with aluminum tube and plastic foot, including cover, Tube length: 800 mm, Number of modules: max. 5 modules, For use with: SL4-L-..., SL4-BL-..., SL4-FL-..., SL4-AP-..., Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, IEC degree of protection: IP66, IEC/EN 60529, Protection type UL: Type 4, 4X, 13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Base module Catalog Number 177313 Model Code SL4-PIB-800 EAN 4015081717668 Product Length/Depth 72 mm Product Height 869 mm Product Width 72 mm Product Weight 0.8 kg

Certifications IEC/EN 60529

IEC/EN 60947-5-1 Features & Functions

Color Other Fitted with: Cover

Aluminum tube

Plastic foot Number of modules Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides)

Max. 5 General

Connection to SmartWire-DT No Degree of protection IP66

NEMA 4

NEMA 4X

NEMA 13 Mounting Method Floor

Horizontal

Bracket Mounting position As required Product Category SL signal towers Rated impulse withstand voltage (Uimp) 4000 V

AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Tube length 800 mm Type Base module Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity (AWG) 24 - 16 Terminal capacity (flexible with ferrule and plastic collar) 0.25 - 0.75 mm² Terminal

capacity (solid/flexible) 0.2 - 1.5 mm² Terminal capacity (solid/flexible with ferrule) 0.25 - 1.5 mm² Electrical rating

Rated insulation voltage (Ui) 250 V Rated operational voltage 24 V AC/DC ± 10 %

230/240 V AC ± 10 %

110/120 V AC ± 10 %

ETIM for 177313 Low-voltage industrial contro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-PIB-800 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.