

INDUSTRIAL COMPONENT DATA

SL63032 148583 Y7-148583 EATON ELECTRIC Busbar Mounts, 3p, 20x5-30x10, (60mm)

Brand: EATON - MOELLER | Manufacturer Part Number: SL63032



Manufacturer	EATON - MOELLER
MPN / Reference	SL63032
Catalog number	Y7-148583
Category	Distributor assembly busbars
Minimum order	1 Pcs
Document ID	EO-F973D47395
Generated	2026-08-06

Product Overview

Busbar Mounts, 3p, 20x5-30x10, (60mm)

Eaton xEffect SASy 60i Enclosures Switch- & Controlgear Enclosure. Busbar support, 3p, 20x5-30x10, (60mm)

Busbar support for distribution system EP, 60 mm system, rated operational current $I_e=630A$, poles=3, can be used for 20x5/10 to 30x5/10, with removable contact element for adapting to the busbar size, thermoplastic, silicon free, chlorine free, halogen free, distance between busbar supports corresponding to the distribution board's short-circuit strength diagram, expandable to 4 and 5 poles by inserting the 1-pole SLPEN clamp above and below

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASy 60i busbar support Catalog Number 148583 Model Code SL63032 EAN 4015081450312 Product Length/Depth 40 mm Product Height 180 mm Product Width 15 mm Product Weight 0.08 kg

Compliances RoHS conform Delivery program

Number of poles Three-pole Technical data - electrical

Current rating - max 630 A Rated short-time withstand current (I_{cw}) 40.5 kA Technical data - mechanical

Busbar distance 60 mm Busbar height 10 mm Busbar position Above center Busbar thickness - max 30 mm

ETIM for 148583 Power distribution systems (EC001896)

Feature Name

Feature Value

Height (EF000040)
180 mm
Width (EF000008)
15 mm
Depth (EF000049)
40 mm
With cover (EF000361)
No
Number of poles (EF001391)
3
Busbar distance (EF002638)
60 mm
Rail height (EF002639)
10 mm
Busbar thickness (EF002640)
30 mm
Max. rated current (EF007926)
630 A
Short-circuit breaking capacity (I_{cw}) (EF002562)
40.5 kA
Busbar position (EF009592)
Above centre

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL63032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.