

INDUSTRIAL COMPONENT DATA

M22-SWD-K22LED-R 115981 Y7-115981 EATON ELECTRIC

Illuminated pushbutton function element, SmartWire-DT, 2W,

..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-SWD-K22LED-R



Manufacturer	EATON - MOELLER
MPN / Reference	M22-SWD-K22LED-R
Catalog number	Y7-115981
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-E99A24AD42
Generated	2026-08-03

Product Overview

Illuminated pushbutton function element, SmartWire-DT, 2W, LED, red, front mount

M22-SWD-K22LED-R

Function element, for combination with RMQ-Titan operating elements M22-..., 2 changeover contact, Front fixing, red

Function element, Fixing: Front fixing, Connection to SmartWire-DT: yes

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Function element, for combination with RMQ-Titan operating elements M22-..., 2 changeover contact, Front fixing,

redFunction element, Fixing: Front fixing, Connection to SmartWire-DT: yes

General specificationsProduct nameEaton Moeller® series M22 Function elementPart

no.M22-SWD-K22LED-REAN4015081157211Product Length/Depth45 millimetreProduct height42 millimetreProduct

width17 millimetreProduct weight0.013 kilogramCertificationsEN 50178

CSA Class No.: 3211-07

UL File No.: E29184

UL

UL Category Control No.: NKCR

CSA

IEC/EN 61131-2

CSA File No.: 2324643

BV

LRSPProduct TradenameM22Product TypeFunction elementProduct Sub TypeNoneFeatures & FunctionsElectric connection typeFlat plug-in connectionFunctionsFor combination with RMQ-Titan operating elements M22-...

Diagnosis functionGeneral informationDegree of protectionIP20ModelTop mountingMounting methodFront fasteningOvervoltage categoryNot applicablePollution degree2Product categorySmartWire-DT RMQ connectionsAmbient conditions, mechanicalConstant acceleration1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, VibrationsConstant amplitude3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, VibrationsDrop and topple50 mm Drop height, Drop to IEC/EN 60068-2-31Height of fall (IEC/EN 60068-2-32) - max0.3 mMounting positionAs requiredShock resistance15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 ImpactsClimatic environmental conditionsAmbient operating temperature - min-30 °CAmbient operating temperature - ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-SWD-K22LED-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.