

INDUSTRIAL COMPONENT DATA

SWD4-10LF8-24-2S 116029 Y7-116029 EATON ELECTRIC Flat cable, SmartWire-DT, 10m, 8-Pole, prefabricated with 2..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-10LF8-24-2S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-10LF8-24-2S
Catalog number	Y7-116029
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-FE25F0477A
Generated	2026-08-03

Product Overview

Flat cable, SmartWire-DT, 10m, 8-Pole, prefabricated with 2 blade terminals SWD4-8MF2

SWD4-10LF8-24-2S

SmartWire-DT ribbon cable for connecting SmartWire-DT participants within the control panel, 10 m, 8-Pole, prefabricated with 2 blade terminals SWD4-8MF2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Flat cable Catalog Number 116029 Model Code SWD4-10LF8-24-2S EAN 4015081157693 Product Length/Depth 130 mm Product Height 22 mm Product Width 130 mm Product Weight 0.345 kg

Certifications CSA Class No.: 3211-07

UL

UL Category Control No.: NKCR

CSA

UL File No.: E29184

CSA File No.: 2324643 Features & Functions

Features Longitudinal water blocking cable

UV resistant Fitted with: 2 blade terminals SWD4-8MF2 Functions For connecting the SmartWire-DT modules within the control panel General

Cable length 10 m Number of Poles Eight-pole Outer diameter - approximate 17.5 mm Outer sheath material Polyvinyl chloride (PVC) Permitted bending radius, moving application with forced guidance - min 15 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Safety Flame retardant In accordance with EN 60332-1-2 Design verification Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-10LF8-24-2S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.