

INDUSTRIAL COMPONENT DATA

SWD4-3LF8-24-2S 116027 Y7-116027 EATON ELECTRIC Flat cable, SmartWire-DT, 3m, 8-Pole, prefabricated with 2 b..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-3LF8-24-2S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-3LF8-24-2S
Catalog number	Y7-116027
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-1E0F5B1225
Generated	2026-07-28

Product Overview

Flat cable, SmartWire-DT, 3m, 8-Pole, prefabricated with 2 blade terminals SWD4-8MF2

SWD4-3LF8-24-2S

SmartWire-DT ribbon cable for connecting SmartWire-DT participants within the control panel, 3 m, 8-Pole, prefabricated with 2 blade terminals SWD4-8MF2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Flat cable Catalog Number 116027 Model Code SWD4-3LF8-24-2S EAN 4015081157679 Product Length/Depth 90 mm Product Height 22 mm Product Width 90 mm Product Weight 0.11 kg

Certifications UL

UL File No.: E29184

UL Category Control No.: NKCR

CSA File No.: 2324643

CSA Class No.: 3211-07

CSA Features & Functions

Fitted with: 2 blade terminals SWD4-8MF2 Functions For connecting the SmartWire-DT modules within the control panel

General

Cable length 3 m Number of Poles Eight-pole Outer diameter - approximate 17.5 mm Outer sheath material Polyvinyl

chloride (PVC) Permitted bending radius, moving application with forced guidance - min 15 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Safety Flame retardant In accordance with EN 60332-1-2 Design verification Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-3LF8-24-2S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.