

INDUSTRIAL COMPONENT DATA

SWD4-8MF2 116023 Y7-116023 EATON ELECTRIC Blade terminal, SmartWire-DT, on ribbon-cable end for connecting C..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-8MF2



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-8MF2
Catalog number	Y7-116023
Category	Accessories/spare parts for controls
Minimum order	10 Pcs
Document ID	EO-3FD6CEF0BD
Generated	2026-08-02

Product Overview

Blade terminal, SmartWire-DT, on ribbon-cable end for connecting coordinator etc.

SWD4-8MF2

SmartWire-DT blade terminal, 8 pole, is attached to both ends of the SWD ribbon cable. The following component can be attached: SmartWire-DT coordinators such as easy800 SWD/SWD Gateway, SWD-Power feeder module, SWD coupling, SWD bus termination

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Smartwire Darwin**

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Blade terminal Catalog Number 116023 Model Code SWD4-8MF2 EAN 4015081157631 Product Length/Depth 8 mm Product Height 18 mm Product Width 23 mm Product Weight 0.002 kg

Certifications UL File No.: E29184

CSA

CSA File No.: 2324643

CSA Class No.: 3211-07

UL Category Control No.: NKCR

UL Catalog Notes not relevant Features & Functions

Functions For connecting the ribbon cable to the gateway, power feeder module, coupling, SWD4-RC8-10 bus termination resistor General

Degree of protection IP20

IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Product category SmartWire-DT accessories Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 105 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 105 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures

Operating temperature - min -25 °C Operating temperature - max 105 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-8MF2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.