

INDUSTRIAL COMPONENT DATA

SWD4-8SF2-5 116022 Y7-116022 EATON ELECTRIC External device plug, SmartWire-DT, at ribbon cable for connecti..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-8SF2-5



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-8SF2-5
Catalog number	Y7-116022
Category	Accessories/spare parts for controls
Minimum order	10 Pcs
Document ID	EO-A2EF1C5C75
Generated	2026-07-29

Product Overview

External device plug, SmartWire-DT, at ribbon cable for connection of SWD module SWD4-8SF2-5

External device plug, 8-Pole can be attached at any arbitrary place on the ribbon cable. The functional elements of arbitrarily many SmartWire-DT cards can be attached to the external device plug.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory External device plug Catalog Number 116022 Model Code SWD4-8SF2-5 EAN 4015081157624 Product Length/Depth 17 mm Product Height 36 mm Product Width 15 mm Product Weight 0.006 kg

Certifications CSA File No.: 2324643

IEC/EN 61131-2

UL File No.: E29184

EN 50178

CSA Class No.: 3211-07

UL

UL Category Control No.: NKCR

CSA Catalog Notes not relevant Features & Functions

Functions For connecting the ribbon cable to SmartWire-DT modules in the control panel General

Degree of protection IP20 (according to IEC/EN 60529, EN 50178, VBG 4)

IP20 Product category SmartWire-DT accessories Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures

Operating temperature - min -25 °C Operating temperature - max 55 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) Electrical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-8SF2-5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.