

INDUSTRIAL COMPONENT DATA

SWD4-FFR-PF1-1 168880 Y7-168880 EATON ELECTRIC Feeder module, SmartWire-DT, supply for contactors/cards of a..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-FFR-PF1-1



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-FFR-PF1-1
Catalog number	Y7-168880
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-0D560DD0D6
Generated	2026-08-03

Product Overview

Feeder module, SmartWire-DT, supply for contactors/cards of a local SWD segment

SWD4-FFR-PF1-1

Module for surface mounting of a local SWD segment in in connection with line adapter SWD4-FFR-ST1-1, SmartWire-DT card's supply as well as control voltage feeder for the motor starter and contactors, protected against overload and short-circuit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Power supply Catalog Number 168880 Model Code SWD4-FFR-PF1-1 EAN 4015081653713 Product Length/Depth 45 mm Product Height 90 mm Product Width 72 mm Product Weight 0.105 kg Certifications IEC/EN 61131-2

EN 50178 Catalog Notes SWD power supply module for modules (IP20) on a local SWD segment Features & Functions Electric connection type Flat plug-in connection Features Fieldbus connection over separate bus coupler possible Fitted with: Power supply module General

Degree of protection IP20 Mounting method Rail mounting possible

Wall mounting/direct mounting

Top-hat rail fixing (according to IEC/EN 60715, 35 mm)

Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Product category SmartWire-DT accessories Suitable as

Segment module Type SWD power supply module Voltage type DC Ambient conditions, mechanical
Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz,
according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to
IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions
Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max
55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to
IEC 60068-2-2
Damp heat, constant, to IEC 60068-2-3 Env...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-FFR-PF1-1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.