

INDUSTRIAL COMPONENT DATA

SWD4-SM8-20 116032 Y7-116032 EATON ELECTRIC Housing bushing socket, SmartWire-DT, plug, M20, for SWD4-SF8 so..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-SM8-20



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-SM8-20
Catalog number	Y7-116032
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-30E10BCE18
Generated	2026-08-02

Product Overview

Housing bushing socket, SmartWire-DT, plug, M20, for SWD4-SF8 socket for round cable
SWD4-SM8-20

Enclosure bushing for flush mounting in surface mounting enclosure M22-I..., 8 pole plug for connection on
SWD4-SF8-67(W), enclosure degree of protection IP67 8 prefabricated cables for connection to card M22-SWD-I...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Housing bushing socket Catalog Number 116032 Model Code SWD4-SM8-20 EAN 4015081157723 Product Length/Depth 144 mm Product Height 24 mm Product Width 24 mm Product Weight 0.026 kg

Certifications UL File No.: E29184

CSA Class No.: 3211-07

UL

UL Category Control No.: NKCR

CSA

CSA File No.: 2324643

EN 50178

IEC/EN 61131-2 Catalog Notes not relevant General

Degree of protection IP20 (according to IEC/EN 60529, EN 50178, VBG 4)

IP20 Product category SmartWire-DT accessories Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures

Operating temperature - min -25 °C Operating temperature - max 55 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) Communication

Connection type Connection 2: SWD-OUT, 8 cables

Connection 1: M20 Plug, 8-pole Input/Output

Number of insertion cycles 500 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-SM8-20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.