

INDUSTRIAL COMPONENT DATA

S811+V10P3S 169012 S811PLUSV10P3S EATON ELECTRIC

Soft starter, 3p, 1000A, Ue 200-600VAC

Brand: EATON - MOELLER | Manufacturer Part Number: S811+V10P3S



Manufacturer	EATON - MOELLER
MPN / Reference	S811+V10P3S
Catalog number	Y7-169012
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-F57B9A4164
Generated	2026-08-05

Product Overview

Soft starter, 3p, 1000A, Ue= 200-600VAC

Soft starter, 1000 A, 200 - 600 V AC, Us= 24 V DC, with control unit and pump algorithm, Frame size V

Soft starters, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit and pump algorithm, Mains supply voltage (50/60 Hz): ULN= 200 - 600 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 560 kW, at 460 V, 60 Hz: P= 750 HP, Rated operational current AC-53: Ie= 1000 A, Rated operational current AC-53, In-Delta: Ie= 1732 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V , 600 V, Connection to SmartWire-DT: no, Frame size: V, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14-1995, GB14048

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > High Performance Soft Starters**

Additional Product Information

General specifications

Product Name Eaton S811+ soft starter Catalog Number 169012 Model Code S811+V10P3S EAN 4015081655052 UPC 786680238277 Product Length/Depth 187.8 mm Product Height 420.8 mm Product Width 280.6 mm Product Weight 41.4 kg Certifications CE Product specifications

Type Soft starter Fitted with: Internal bypass

Motor overload protection

Display Class Adjustable Ambient operating temperature - max 50 °C Voltage type DC Rated operational voltage (Ue) - min 200 V Rated power three-phase motor, inline, at 230 V 200 kW Rated power three-phase motor, inline, at 400 V 560 kW Rated power three-phase motor, inside delta, at 230 V 200 kW Rated power three-phase motor, inside delta, at 400 V 900 kW Degree of protection IP20

NEMA Other Functions Single direction Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at DC - max 24 V Rated control supply voltage (Us) at DC - min 24 V Rated operational current (Ie) at AC-53 1000 A Rated operational voltage (Ue) - max 600 V

ETIM for 169012 Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Rated operation current Ie at 40 °C Tu (EF007039)

1000 A

Rated operating voltage Ue (EF002418)

200 V

Rated power three-phase motor, inline, at 230 V (EF007053)

200 kW

Rated power three-phase motor, inl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S811+V10P3S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.