

**INDUSTRIAL COMPONENT DATA**

# S811+T24N3S 168987 S811PLUST24N3S EATON ELECTRIC

## Soft starter, 3p, 240A, Ue 200-600VAC

Brand: EATON - MOELLER | Manufacturer Part Number: S811+T24N3S



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | S811+T24N3S     |
| Catalog number  | S811PLUST24N3S  |
| Category        | Soft starter    |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-455319EB5D   |
| Generated       | 2026-08-05      |

### Product Overview

Soft starter, 3p, 240A, Ue= 200-600VAC

Soft starter, 240 A, 200 - 600 V AC, Us= 24 V DC, with control unit, Frame size T

Soft starter, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit, Mains supply voltage (50/60 Hz): ULN= 200 - 600 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 132 kW, at 460 V, 60 Hz: P= 200 HP, Rated operational current AC-53: Ie= 240 A, Rated operational current AC-53, In-Delta: Ie= 415 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V, 600 V, Connection to SmartWire-DT: no, Frame size: T, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14-1995, GB14048

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > High Performance Soft Starters**

### Additional Product Information

EL-Nummer (Norway)4137471Soft starter, 240 A, 200 - 600 V AC, Us= 24 V DC, with control unit, Frame size TSoft starter, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit, Mains supply voltage (50/60 Hz): ULN= 200 - 600 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 132 kW, at 460 V, 60 Hz: P= 200 HP, Rated operational current AC-53: Ie= 240 A, Rated operational current AC-53, In-Delta: Ie= 415 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V,

400 V, 480 V, 600 V, Connection to SmartWire-DT: no, Frame size: T, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14-1995, GB14048 Delivery program

This item is only available for a limited time and will be replaced by the following item: 168988, S811+T24P3S Description With internal bypass contacts Function Soft starter for three-phase loads, with control unit Mains supply voltage (50/60 Hz) [ULN]200 - 600 V AC Supply voltage [Us]24 V DC Control voltage [UC]24 V DC Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz [P]132 kW at 460 V, 60 Hz [P]200 HP Rated operational current AC-53 [Ie]240 AAC-53, In-Delta [Ie]415 A Startup class CLASS 10 (star-delta repl...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S811+T24N3S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.