

INDUSTRIAL COMPONENT DATA

S811+T24P3S 168988 Y7-168988 EATON ELECTRIC Soft starter, 3p, 240A, Ue 200-600VAC

Brand: EATON - MOELLER | Manufacturer Part Number: S811+T24P3S



Manufacturer	EATON - MOELLER
MPN / Reference	S811+T24P3S
Catalog number	Y7-168988
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-880E50B576
Generated	2026-08-06

Product Overview

Soft starter, 3p, 240A, Ue= 200-600VAC

S811+T24P3S

Eaton S811 Soft starter, 240 A, 200 - 600 V AC, Us= 24 V DC, with control unit and pump algorithm, Frame size T

Soft starter, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit and pump algorithm, Mains supply voltage (50/60 Hz): ULN= 200 - 600 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 132 kW, at 460 V, 60 Hz: P= 200 HP, Rated operational current AC-53: Ie= 240 A, Rated operational current AC-53, In-Delta: Ie= 415 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V , 600 V, Connection to SmartWire-DT: no, Frame size: T, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > High Performance Soft Starters**

Additional Product Information

General specifications

Product Name Eaton S811 Soft starter Catalog Number 168988 Model Code S811+T24P3S EAN 4015081654833 Product

Length/Depth 164.4 mm Product Height 322.9 mm Product Width 194.4 mm Product Weight 18.6 kg Compliances CE

Marked Certifications EN 60947-4-2

UL Recognized

UL Listed

IEC 60947-4-2
CSA file No. 3211-06
CSA Certified for Elevator Duty
IEC/EN 60947-4-2
GB14048
CE
UL 508
UL Category Control No.: NMFT
CSA
UL File No.: E202571
CSA File No.: LR 353
CCC
CSA Class No.: 3211-06, 2411-01
CSA-C22.2 No. 14
UL
C-Tick
CSA22.2-14-1995 Features & Functions
Fault memory 10 Faults Fitted with: Internal bypass contacts
Motor overload protection
Display
Internal bypass Functions Potential isolation between power and control sections
Underload monitoring
Current limitation
Suppression of DC components for motors
Min. ramp time 1 s - fast switching (semiconductor contactor)
Soft start function
Overload monitoring
Single direction
Suppression of closing transients Interfaces Modbus RTU (built-in) General
Class Adjustable Connection to SmartWire-DT No Degree of protection IP00
NEMA Other Frame size T Mains voltage - min 200 V Mains voltage - max 600 V Mounting position As required
Overvoltage category II Pollution degree 3 Radio interference class Class A (EN 55011) Rated impulse withstand voltage (Uimp) 4000 V Rated insulation voltage (Ui) 660 V Shock resistance 15 g, Mechanical Startup class CLASS 10 (star-delta replacement)
CLASS 20 (heavy starting duty 3 x Ie for 45....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S811+T24P3S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.