

INDUSTRIAL COMPONENT DATA

S811+V36V3S 168995 Y7-168995 EATON ELECTRIC Soft starter, 3p, 360A, Ue 575-690VAC

Brand: EATON - MOELLER | Manufacturer Part Number: S811+V36V3S



Manufacturer	EATON - MOELLER
MPN / Reference	S811+V36V3S
Catalog number	Y7-168995
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-50252E3A20
Generated	2026-08-04

Product Overview

Soft starter, 3p, 360A, Ue= 575-690VAC

S811+V36V3S

Eaton S811 Soft starter, 361 A, 200 - 690 V AC, Us= 24 V DC, with control unit and pump algorithm, for 690-V grids, Frame size V

Soft starter, Description: With internal bypass contacts, Function: Soft starter for three-phase loads, with control unit and pump algorithm, for 690-V grids, Mains supply voltage (50/60 Hz): ULN= 200 - 690 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 200 kW, at 690 V, 50 Hz: P= 315 kW, at 460 V, 60 Hz: P= 300 HP, Rated operational current AC-53: Ie= 361 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), CLASS 30 (6 x Ie for 30 s), Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V, 600 V, 690 V, Connection to SmartWire-DT: no, Frame size: V, Ordering information: Terminal blocks for the terminals are required for frame sizes T, U, and V -

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > High Performance Soft Starters

Additional Product Information

General specifications

Product Name Eaton S811 Soft starter Catalog Number 168995 Model Code S811+V36V3S EAN 4015081654901 Product Length/Depth 187.8 mm Product Height 420.8 mm Product Width 280.6 mm Product Weight 41.4 kg Certifications C-Tick UL Category Control No.: NMFT GB14048

CE

UL File No.: E202571

UL 508

CSA22.2-14-1995

UL

CCC

CSA

IEC/EN 60947-4-2 Features & Functions

Fault memory 10 Faults Fitted with: Display

Internal bypass contacts

Internal bypass

Motor overload protection Functions Suppression of closing transients

Underload monitoring

Min. ramp time 1 s - fast switching (semiconductor contactor)

Soft start function

Current limitation

Potential isolation between power and control sections

Overload monitoring

Suppression of DC components for motors

Single direction Interfaces Modbus RTU (built-in) General

Class Adjustable Connection to SmartWire-DT No Degree of protection IP00

NEMA Other Frame size V Mains voltage - min 200 V Mains voltage - max 690 V Mounting position As required

Overvoltage category II Pollution degree 3 Radio interference class Class A (EN 55011) Rated impulse withstand voltage (Uimp) 4000 V Shock resistance 15 g, Mechanical Startup class CLASS 20 (heavy starting duty 3 x Ie for 45 s)

CLASS 30 (6 x Ie for 30 s)

CLASS 10 (star-delta replacement) Suitable for Branch circuits, not as BCPD, (UL/CSA) Type Soft starter for three-phase loads, with control unit and pump algorithm, for 690-V grids Voltage type DC Climatic environmental conditions

Altit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S811+V36V3S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.