

INDUSTRIAL COMPONENT DATA

DS6-340-37K-MX 103088 EATON ELECTRIC Soft starter, 68 A, 230 480 V AC, Us 24 V DC

Brand: EATON - MOELLER | Manufacturer Part Number: DS6-340-37K-MX



Manufacturer	EATON - MOELLER
MPN / Reference	DS6-340-37K-MX
Catalog number	103088
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-569EAEC9FE
Generated	2026-08-04

Product Overview

Soft starter, 68 A, 230 - 480 V AC, Us= 24 V DC

Description: With internal bypass contacts, Function: Soft starters for three-phase loads, Mains supply voltage (50/60 Hz): ULN= 230 - 480 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 37 kW, at 460 V, 60 Hz: P= 50 HP, Rated operational current AC-53: Ie= 68 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), Rated operational voltage: Ue= 230 V, 400 V, 480 V, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14, GB14048

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Soft starter, 68 A, 230 - 480 V AC, Us= 24 V DC Eaton Catalog No. DS6-340-37K-MX Description: With internal bypass contacts, Function: Soft starters for three-phase loads, Mains supply voltage (50/60 Hz): ULN= 230 - 480 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 37 kW, at 460 V, 60 Hz: P= 50 HP, Rated operational current AC-53: Ie= 68 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), Rated operational voltage: Ue= 230 V, 400 V, 480 V, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14, GB14048 [Delivery program

Description With internal bypass contacts Function Soft starters for three-phase loads Mains supply voltage (50/60 Hz) [ULN] 230 - 480 V AC Supply voltage [Us] 24 V DC Control voltage [UC] 24 V DC Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz [P] 37 kW at 460 V, 60 Hz [P] 50 HP Rated operational current AC-53 [Ie] 68 A Startup class CLASS 10 (star-delta replacement)

CLASS 20 (heavy starting duty 3 x I_{ef} for 45 s) Rated operational voltage [U_e] 230 V
400 V

480 V , Technical data

General Standards IEC/EN 60947-4-2

UL 508

CSA22.2-14

GB14048 Approvals CE Approvals UL

CSA

C-Tick

UkrSEPRO

CCC Climatic proofing Damp heat, constant, to IEC 60068-2-3

Damp heat, cyclic, to IEC 60068-2-10 Ambient temperature Operation [?] 0 - +40

up to 60 at 1 % derating per Kelvin temperature rise °C Ambient temperature Storage [?] -2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS6-340-37K-MX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.