

INDUSTRIAL COMPONENT DATA

DS6-340-55K-MX 103150 EATON ELECTRIC SOFT STARTER 55KW

Brand: EATON - MOELLER | Manufacturer Part Number: DS6-340-55K-MX



Manufacturer	EATON - MOELLER
MPN / Reference	DS6-340-55K-MX
Catalog number	103150
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-F0E9D53948
Generated	2026-08-04

Product Overview

SOFT STARTER 55KW

Description: With internal bypass contacts, Function: Soft starters for three-phase loads, Mains supply voltage (50/60 Hz): ULN= 230 - 480 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 55 kW, at 460 V, 60 Hz: P= 75 HP, Rated operational current AC-53: Ie= 99 A, Startup class: CLASS 10 (star-delta replacement), CLASS 20 (heavy starting duty 3 x Ie for 45 s), Rated operational voltage: Ue= 230 V, 400 V, 480 V, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14, GB14048

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery programme Description With internal bypass contacts

Function Soft starters for three-phase loads

Mains supply voltage (50/60 Hz) ULN V AC 230 - 480

Supply voltage Us 24 V DC

Control voltage UC 24 V DC

Assigned motor rating (Standard connection, In-Line)

at 400 V, 50 Hz P kW 55

at 460 V, 60 Hz P HP 75

Rated operational current

AC-53 Ie A 99

Startup class CLASS 10 (star-delta replacement)

CLASS 20 (heavy starting duty 3 x I_e for 45 s)

Rated operational voltage U_e 230 V

400 V

480 V

Technical data General

Standards IEC/EN 60947-4-2

UL 508

CSA22.2-14

GB14048

Approvals CE

Approvals UL

CSA

C-Tick

UkrSEPRO

CCC

Climatic proofing Damp heat, constant, to IEC 60068-2-3

Damp heat, cyclic, to IEC 60068-2-10

Ambient temperature

Operation ? °C 0 - +40

up to 60 at 1 % derating per Kelvin temperature rise

Storage ? °C -25 - +55

Altitude m 0 - 1000 m, above that 1 % derating per 100 m , up to 2000 m

Mounting position Vertical

Degree of protection

Degree of Protection IP20 (terminals IP00)

Integrated Protection type IP40 can be achieved on all sides with covers from the NZM range.

Protection against direct contact Finger and back-of-hand proof

Overvoltage category/pollution degree II/2

Shock resistance 8 g/11 ms

Vibration resistance to EN 60721-3-2 2M2

Radio interference level (IEC/EN 55011) A

Weight kg 1.8

Main conducting paths

Rated operating voltage U_e V AC 230 - 480

Supply frequency f_{LN} Hz 50/60

Rated operational current I_e A

AC-53 I_e A 99

Assigned motor rating (Standard connection,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS6-340-55K-MX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.