

INDUSTRIAL COMPONENT DATA

DS7-342SX070N0-N 134936 Y7-134936 EATON ELECTRIC Soft starter, 70 A, 200 480 V AC, Us 110 230 V AC, Frame si..

Brand: EATON - MOELLER | Manufacturer Part Number: DS7-342SX070N0-N



Manufacturer	EATON - MOELLER
MPN / Reference	DS7-342SX070N0-N
Catalog number	Y7-134936
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-70878B48DF
Generated	2026-08-05

Product Overview

Soft starter, 70 A, 200 - 480 V AC, Us= 110 - 230 V AC, Frame size FS3

DS7-342SX070N0-N

Soft starter, Description: With internal bypass contacts, Function: Soft starters for three-phase loads, Mains supply voltage (50/60 Hz): ULN= 200 - 480 V AC, Supply voltage: Us= 110 - 230 V AC, Control voltage: UC= 110 - 230 V AC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 37 kW, at 460 V, 60 Hz: P= 50 HP, Rated operational current AC-53: Ie= 70 A, Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V, Connection to SmartWire-DT: no, Frame size: FS3, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Standard Soft Starters**

Additional Product Information

General specifications

Product Name Eaton DS7 Soft starter Catalog Number 134936 Model Code DS7-342SX070N0-N EAN 4015081317516

Product Length/Depth 139 mm Product Height 175 mm Product Width 93 mm Product Weight 1.8 kg Certifications

CSA22.2-14

CSA Class No.: 321106

GB 14048.6

CSA-C22.2 No 0-M91

CSA

IEC/EN 60947-4-2

C-Tick

UL File No.: E251034

UL

CE

UL 508

UkrSEPRO

CSA File No.: 2511305

CSA-C22.2 No 14-05 Features & Functions

Fitted with: Internal bypass

Internal bypass contacts Functions Suppression of closing transients

Suppression of DC components for motors

Soft start function

Min. ramp time 1 s - fast switching (semiconductor contactor)

Potential isolation between power and control sections

Single direction General

Class Other Connection to SmartWire-DT No Degree of protection NEMA 1

IP20 Frame size FS3 Mains voltage - max 480 V Mains voltage - min 200 V Overvoltage category II Pollution degree 2

Radio interference class Class A (EN 55011) Suitable for Branch circuits, (UL/CSA) Type Soft starter for three-phase loads

Voltage type AC Ambient conditions, mechanical

Mounting position Vertical Shock resistance 8 g, 11 ms, Mechanical Vibration resistance 2M2 to EN 60721-3-2 Climatic environmental conditions

Altitude Above 1000 m with 1 % derating per 100 m

Max. 2000 m Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-3 Main conducting paths

Overload cy...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS7-342SX070N0-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.