

**INDUSTRIAL COMPONENT DATA**

# DS7-340SX070N0-N 134918 Y7-134918 EATON ELECTRIC Soft starter, 70 A, 200 480 V AC, Us 24 V AC/DC, Frame size..

Brand: EATON - MOELLER | Manufacturer Part Number: DS7-340SX070N0-N



|                 |                  |
|-----------------|------------------|
| Manufacturer    | EATON - MOELLER  |
| MPN / Reference | DS7-340SX070N0-N |
| Catalog number  | Y7-134918        |
| Category        | Soft starter     |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-CE6B78F2E7    |
| Generated       | 2026-08-06       |

## Product Overview

Soft starter, 70 A, 200 - 480 V AC, Us= 24 V AC/DC, Frame size FS3

DS7-340SX070N0-N

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Standard Soft Starters**

## Additional Product Information

General specifications

Product Name Eaton DS7 Soft starter Catalog Number 134918 Model Code DS7-340SX070N0-N EAN 4015081317332

Product Length/Depth 139 mm Product Height 175 mm Product Width 93 mm Product Weight 1.8 kg Compliances CE

Marked

C-Tick Compliant Certifications CSA Certified

IEC 60947-4-2

EN 60947-4-2

UL Listed

C-Tick

UkrSEPRO

CSA

CE

UL 508

IEC/EN 60947-4-2

UL  
UL File No.: E251034  
CSA File No.: 2511305  
CSA Class No.: 321106  
CSA22.2-14  
CSA-C22.2 No 14-05  
GB 14048.6  
CSA-C22.2 No 0-M91 Features & Functions  
Fitted with: Internal bypass  
Internal bypass contacts Functions Potential isolation between power and control sections  
Single direction  
Min. ramp time 1 s - fast switching (semiconductor contactor)  
Suppression of DC components for motors  
Soft start function  
Suppression of closing transients General  
Class Other Connection to SmartWire-DT No Degree of protection NEMA 1  
IP20 Frame size 3  
4  
FS3 Mains voltage - max 480 V Mains voltage - min 200 V Overvoltage category II Pollution degree 2 Radio interference class Class B (EN 55011) Suitable for Branch circuits, (UL/CSA) Type Soft starter for three-phase loads Voltage type AC/DC Ambient conditions, mechanical  
Mounting position Vertical Shock resistance 8 g, 11 ms, Mechanical Vibration resistance 2M2 to EN 60721-3-2 Climatic environmental conditions  
Altitude Max. 2000 m  
Above 1000 m with 1 % derating per 100 m Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Climatic proofing Damp heat,....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS7-340SX070N0-N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.