

INDUSTRIAL COMPONENT DATA

DS7-340SX081N0-N 134919 Y7-134919 EATON ELECTRIC Soft starter, 81 A, 200 480 V AC, Us 24 V AC/DC, Frame size..

Brand: EATON - MOELLER | Manufacturer Part Number: DS7-340SX081N0-N



Manufacturer	EATON - MOELLER
MPN / Reference	DS7-340SX081N0-N
Catalog number	Y7-134919
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-EEEE46E6B7
Generated	2026-08-05

Product Overview

Soft starter, 81 A, 200 - 480 V AC, Us= 24 V AC/DC, Frame size FS3

DS7-340SX081N0-N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Standard Soft Starters**

Additional Product Information

General specifications

Product Name Eaton DS7 Soft starter Catalog Number 134919 Model Code DS7-340SX081N0-N EAN 4015081317349

Product Length/Depth 139 mm Product Height 175 mm Product Width 93 mm Product Weight 1.8 kg Compliances CE

Marked

C-Tick Compliant Certifications UL Listed

IEC 60947-4-2

EN 60947-4-2

CSA Certified

CE

UL 508

C-Tick

CSA22.2-14

CSA File No.: 2511305

GB 14048.6

CSA Class No.: 321106

UkrSEPRO

UL File No.: E251034

CSA-C22.2 No 0-M91

CSA

UL

IEC/EN 60947-4-2

CSA-C22.2 No 14-05 Features & Functions

Fitted with: Internal bypass contacts

Internal bypass Functions Min. ramp time 1 s - fast switching (semiconductor contactor)

Suppression of closing transients

Soft start function

Suppression of DC components for motors

Potential isolation between power and control sections

Single direction General

Class Other Connection to SmartWire-DT No Degree of protection IP20

NEMA 1 Frame size 3

4

FS3 Mains voltage - max 480 V Mains voltage - min 200 V Overvoltage category II Pollution degree 2 Radio interference class Class B (EN 55011) Suitable for Branch circuits, (UL/CSA) Type Soft starter for three-phase loads Voltage type

AC/DC Ambient conditions, mechanical

Mounting position Vertical Shock resistance 8 g, 11 ms, Mechanical Vibration resistance 2M2 to EN 60721-3-2 Climatic environmental conditions

Altitude Above 1000 m with 1 % derating per 100 m

Max. 2000 m Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Climatic proofing

Damp heat,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS7-340SX081N0-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.