

INDUSTRIAL COMPONENT DATA

DS7-34DSX135N0-D 134957 Y7-134957 EATON ELECTRIC Soft starter, 135 A, 200 480 V AC, 24 V DC, Frame size: FS4..

Brand: EATON - MOELLER | Manufacturer Part Number: DS7-34DSX135N0-D



Manufacturer	EATON - MOELLER
MPN / Reference	DS7-34DSX135N0-D
Catalog number	Y7-134957
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-954433C9CC
Generated	2026-08-06

Product Overview

Soft starter, 135 A, 200 - 480 V AC, 24 V DC, Frame size: FS4, Communication Interfaces: SmartWire-DT
DS7-34DSX135N0-D

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Standard Soft Starters**

Additional Product Information

General specifications

Product Name Eaton DS7 Soft starter Catalog Number 134957 Model Code DS7-34DSX135N0-D EAN 4015081317721

Product Length/Depth 195 mm Product Height 215 mm Product Width 108 mm Product Weight 3.7 kg Warranty

Compliances CE Marked

C-Tick Compliant Certifications UL Listed

EN 60947-4-2

IEC 60947-4-2

CSA Certified

CSA-C22.2 No 0-M91

CSA-C22.2 No 14-05

C-Tick

IEC/EN 60947-4-2

CSA22.2-14

CSA

UkrSEPRO

UL 508

GB 14048.6

CE

UL Features & Functions

Fault memory 8 Faults Fitted with: Internal bypass

Internal bypass contacts Functions Potential isolation between power and control sections

Suppression of closing transients

Suppression of DC components for motors

Soft start function

Current limitation, with PKE

Min. ramp time 1 s - fast switching (semiconductor contactor)

Single direction Interfaces SmartWire-DT (built-in) General

Class Other Connection to SmartWire-DT Yes Degree of protection IP20

NEMA 1 Frame size 3

4

FS4 Mains voltage - max 480 V Mains voltage - min 200 V Overvoltage category II Pollution degree 2 Product category
SmartWire-DT slave Radio interference class Class B (EN 55011) Suitable for Branch circuits, (UL/CSA) Type Soft starter
for three-phase loads Voltage type DC Ambient conditions, mechanical

Mounting position Vertical Shock resistance 8 g, 11 ms, Mechanical Vibration resistance 2M2 to EN 60721-3-2 Climatic
environmental conditions

Altitude Above 1000 m with 1 % derating per 100 m

Max. 2000 m Ambient operating temperature - max 40 °C Ambien...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS7-34DSX135N0-D with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.