

INDUSTRIAL COMPONENT DATA

DS7-34DSX004N0-D 134943 Y7-134943 EATON ELECTRIC Soft starter, 4 A, 200 480 V AC, 24 V DC, Frame size: FS1, ..

Brand: EATON - MOELLER | Manufacturer Part Number: DS7-34DSX004N0-D



Manufacturer	EATON - MOELLER
MPN / Reference	DS7-34DSX004N0-D
Catalog number	Y7-134943
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-D07BD7CCF1
Generated	2026-08-04

Product Overview

Soft starter, 4 A, 200 - 480 V AC, 24 V DC, Frame size: FS1, Communication Interfaces: SmartWire-DT
DS7-34DSX004N0-D

Soft starter, Product range: SmartWire-DT slave, Description: With internal bypass contacts, Function: Soft starters for three-phase loads, Mains supply voltage (50/60 Hz): ULN= 200 - 480 V AC, Supply voltage: Us= 24 V DC, Control voltage: UC= 24 V DC, Assigned motor rating (Standard connection, In-Line) at 400 V, 50 Hz: P= 1.5 kW, at 460 V, 60 Hz: P= 2 HP, Rated operational current AC-53: Ie= 4 A, Rated operational voltage: Ue= 200 V, 230 V, 400 V, 480 V, Connection to SmartWire-DT: yes, Frame size: FS1, Standards: IEC/EN 60947-4-2, UL 508, CSA22.2-14

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Standard Soft Starters

Additional Product Information

General specifications

Product Name Eaton DS7 Soft starter Catalog Number 134943 Model Code DS7-34DSX004N0-D EAN 4015081317585

Product Length/Depth 103 mm Product Height 130 mm Product Width 45 mm Product Weight 0.35 kg Compliances CE

Marked Certifications UL 508

EN 60947-4-2

CSA Std. C22.2 No. 0-M91

CSA Std. C22.2 No. 14-05

IEC 60947-4-2

C-Tick

CSA22.2-14

CSA-C22.2 No 0-M91

CSA

UkrSEPRO

GB 14048.6

UL

IEC/EN 60947-4-2

CE

CSA-C22.2 No 14-05 Features & Functions

Fault memory 8 Faults Fitted with: Internal bypass

Internal bypass contacts Functions Suppression of closing transients

Single direction

Suppression of DC components for motors

Current limitation, with PKE

Potential isolation between power and control sections

Min. ramp time 1 s - fast switching (semiconductor contactor)

Soft start function Interfaces SmartWire-DT (built-in) General

Class Other Connection to SmartWire-DT Yes Degree of protection IP20

NEMA 1 Frame size FS1 Mains voltage - max 480 V Mains voltage - min 200 V Overvoltage category II Pollution degree 2

Product category SmartWire-DT slave Radio interference class Class B (EN 55011) Suitable for Branch circuits, (UL/CSA)

Type Soft starter for three-phase loads Voltage type DC Ambient conditions, mechanical

Mounting position Vertical Shock resistance 8 g, 11 ms, Mechanical Vibration resistance 2M2 to EN 60721-3-2 Climatic environmental conditions

Altitude Max. 2000 m

Above 1000 m with 1 % derating per 100 m Ambient operating temperature - max 40 °C Ambient op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS7-34DSX004N0-D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.