

INDUSTRIAL COMPONENT DATA

DS7-34DSX009N0-D 134946 Y7-134946 EATON ELECTRIC Soft starter, 9 A, 200 480 V AC, 24 V DC, Frame size: FS1, ..

Brand: EATON - MOELLER | Manufacturer Part Number: DS7-34DSX009N0-D



Manufacturer	EATON - MOELLER
MPN / Reference	DS7-34DSX009N0-D
Catalog number	Y7-134946
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-BCA7DA5BF3
Generated	2026-08-03

Product Overview

Soft starter, 9 A, 200 - 480 V AC, 24 V DC, Frame size: FS1, Communication Interfaces: SmartWire-DT
DS7-34DSX009N0-D

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Standard Soft Starters
--------------	--

Additional Product Information

General specifications

Product Name Eaton DS7 Soft starter Catalog Number 134946 Model Code DS7-34DSX009N0-D EAN 4015081317615
Product Length/Depth 103 mm Product Height 130 mm Product Width 45 mm Product Weight 0.35 kg Certifications C-Tick
GB 14048.6
CE
UL 508
IEC/EN 60947-4-2
CSA-C22.2 No 0-M91
UkrSEPRO
CSA
CSA-C22.2 No 14-05
CSA22.2-14
UL Features & Functions
Fault memory 8 Faults Fitted with: Internal bypass

Internal bypass contacts Functions Suppression of DC components for motors
Min. ramp time 1 s - fast switching (semiconductor contactor)
Current limitation, with PKE
Soft start function
Potential isolation between power and control sections
Suppression of closing transients
Single direction Interfaces SmartWire-DT (built-in) General
Class Other Connection to SmartWire-DT Yes Degree of protection IP20
NEMA 1 Frame size FS1 Mains voltage - max 480 V Mains voltage - min 200 V Overvoltage category II Pollution degree 2
Product category SmartWire-DT slave Radio interference class Class B (EN 55011) Suitable for Branch circuits, (UL/CSA)
Type Soft starter for three-phase loads Voltage type DC Ambient conditions, mechanical
Mounting position Vertical Shock resistance 8 g, 11 ms, Mechanical Vibration resistance 2M2 to EN 60721-3-2 Climatic
environmental conditions
Altitude Above 1000 m with 1 % derating per 100 m
Max. 2000 m Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Climatic proofing
Damp heat, constant, to IEC 60068-2-3
Damp heat,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DS7-34DSX009N0-D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.