

INDUSTRIAL COMPONENT DATA

SOL30X4-SAFETY-MC4-U(230V50HZ) 168102 Y7-168102

EATON ELECTRIC Fireman's switch, for 4 strings, 30A, MC4

Brand: EATON - MOELLER | Manufacturer Part Number: SOL30X4-SAFETY-MC4-U(230V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SOL30X4-SAFETY-MC4-U(230V50HZ)
Catalog number	Y7-168102
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-B8017FE06B
Generated	2026-08-04

Product Overview

Fireman's switch, for 4 strings, 30A, MC4

SOL30X4-SAFETY-MC4-U(230V50HZ)

Eaton Moeller® series SOL30 Safety Fireman's switch, for 4 strings, 25A, MC4

Fireman's switch, Degree of Protection: IP65, Standards: IEC/EN 60 947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Solar Switches
--------------	----------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series SOL30 Safety Fireman's switch Catalog Number 168102 Model Code SOL30X4-SAFETY-MC4-U(230V50HZ) EAN 4015081646791 Product Length/Depth 150 mm Product Height 410 mm Product Width 375 mm Product Weight 6.8 kg Certifications IEC/EN 60 947-3 Catalog Notes MC4 connector (Stäubli)

Features & Functions

Actuator type Turn button Enclosure material Plastic Features Complete device in housing Fitted with: 0 (off) position

Retraction in 0-position Number of poles Two-pole General

Application Connection type MC4, Outputs

MC4, Inputs Degree of protection IP65 Degree of protection (front side) IP65

NEMA Other Lifespan, electrical 1,500 Operations Lifespan, mechanical 100,000 Operations Model On/Off switch

Operating frequency 120 Operations/h Overvoltage category III Pollution degree 3 Product Category Fireman's Switch

Switchgear for photovoltaic systems

Rated impulse withstand voltage (Uimp) 8000 V Suitable for Ground mounting Utilization category DC-21 A

DC-PV1 (EN 60947-3)

DC-PV2 (EN 60947-3) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Contacts

Number of auxiliary contacts (change-over contacts) 0 Number of auxiliary contacts (normally closed contacts) 1 Number of auxiliary contacts (normally open contacts) 1 Electrical rating

Rated operational current (Ie) 30 A at....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SOL30X4-SAFETY-MC4-U(230V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.