

INDUSTRIAL COMPONENT DATA

SOLID EXPUL LINK 46SB100 EATON ELECTRIC Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI

Brand: EATON - MOELLER | Manufacturer Part Number: SOLID EXPUL LINK



Manufacturer	EATON - MOELLER
MPN / Reference	SOLID EXPUL LINK
Catalog number	46SB100
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-D1BB097AA3
Generated	2026-08-04

Product Overview

Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI

Ejection Fuse Cartridge, MT, 100 A, AC 46 kV, 787 mm, ANSI

Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, Solid link with fixed NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, Solid link with fixed NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 100 A Rated voltage AC 46 kV Size 787 mm Description Solid link with fixed NEMA button head Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Standard/Approval ANSI

Standards/Regulations ANSI C37-42

ETIM for 46SB100 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated voltage (EF000228)

46 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SOLID EXPUL LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.