

INDUSTRIAL COMPONENT DATA

15KV 100A SOLID LINK 15SU100 EATON ELECTRIC Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 533 mm, AN..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 100A SOLID LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 100A SOLID LINK
Catalog number	15SU100
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-6AD9E38511
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 533 mm, ANSI, style U termination

15KV 100A SOLID LINK

15KV 100A SOLID LINK - Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 8 kA, 533 mm, ANSI, Solid link, universal with slip off NEMA button head

Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 533 mm, ANSI, Solid link, universal with slip off NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15SU100 EAN 5027590435833

Product Length/Depth 102 mm Product Height 233 mm Product Width 77 mm Product Weight 26.2 g Certifications ANSI

Electrical data

Amperage Rating 100 A Voltage rating 15 kV Voltage type AC Current characteristic type Type S - Solid links rated at 100A are also available in both button head and universal versions for fitting into expulsion fuse carriers where required. Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Universal Color None

ETIM for 15SU100 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

100 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Universal

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 100A SOLID LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.