

INDUSTRIAL COMPONENT DATA

**SPPVT2-06-2+PE 176088 Y7-176088 EATON ELECTRIC
Terminal-Set PE/N max. 63A 2x (2x25mm² + 27x16mm²)**

Brand: EATON - MOELLER | Manufacturer Part Number: SPPVT2-06-2+PE



Manufacturer	EATON - MOELLER
MPN / Reference	SPPVT2-06-2+PE
Catalog number	Y7-176088
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-D92AB82478
Generated	2026-08-06

Product OverviewTerminal-Set PE/N max. 63A 2x (2x25mm² + 27x16mm²)

SPPVT2-06-2+PE

Eaton Moeller series xPole - SPPVT2.12 Surge Protection Device. Surge arrester, pluggable, 600V DC, 2-pole+PE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - SPPVT2.12 Surge protection device Catalog Number 176088 Model Code SPPVT2-06-2+PE EAN 4015081712847 Product Length/Depth 90 mm Product Height 65.5 mm Product Width 53.4 mm Product Weight 0.303 kg Compliances RoHS conform Product specifications

Type DC overvoltage protection Surge arrester Special features Pluggable Application Open areas Residential buildings Utility buildings Connection For ungrounded systems Features Category type 2 Frame 3 modular spacing Degree of protection IP20 Equipment heat dissipation, current-dependent 0 W Mounting method DIN rail (top hat rail) 35 mm Voltage protection level (L-N) 0 KV Voltage protection level (N-PE) 0 KV Voltage rating (lu) - max 600 V Signalling at the device Optic System configuration type IT Ambient operating temperature - max 80 °C Ambient operating temperature - min -40 °C Conductor cross section (flexible, fine-strand) - max 0 mm² Conductor cross section (flexible, fine-strand) - min 0 mm² Conductor cross section (solid, solid-strand) - max 0 mm² Conductor cross section (solid, solid-strand) - min 0 mm² Continuous voltage at AC - max 0 V Continuous voltage at DC - max 800 V Discharge surge current (8/20) - max 40 kA Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Nominal discharge surge current (8/20) 15

kA Nominal voltage at AC 0 V Nominal voltage at DC 670 V Number of conductors without earthing 2 PV-voltage - max 800 V Rated oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPPVT2-06-2+PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.